SHINGA

TUBE INSTALLATION TOOLS



TUBE LEAK DETECTOR KIT

FEATURES:

Simple, Quick and Reliable tube testing

Each tube Testing Gun weighs less than 1.0 kg.

Air supply: Uses standard plant air supplies 90 psi (6.0bar)

Air consumption: 26 cfm (720 l/min)

Maximum Vacuum: 80%

Temperature range: -20 C to 80 C Dimension:: 230 x 120 x 170 (mm)



Tube leak detector kit (BVLD-3000) is simple & precise test instrument used by manufacture to indentify tube leakage of condensers, heat e s, boiler and other Tubular apparatus. It is the fastest and most accurate method of locating tube leakage for replacement or plugging or installation of new tubes

It works on the principle of vacuum in which the tool sucks the air from the tube and creates a vacuum to a desired reading on gauge.

Steady reading on gauge indicates NO LEAK.

If the reading on the gauge drops it indicates a tube with a LEAK.



BHARTIYA make BVLD-3000 Leak Detector Test Kit include:

Vacuum Gun: 1 No. Tube Seal with Nozzle (Any one size): 1 set. T handle with plugging nozzle & plugging seal : 1 set Pneumatic Hose: 2 meter Compact Carrying Case: 1 Pc.

SPARES MODEL NO.

Tube S	ize Mm	Seal Model No.	Nozzle Handle Side Model	Nozzle Gun Side Model
6.4-19.05	1-4"-3/4"	P-750	NH-750	NG-750
15.9-31.7	5.8"/1.1/4"	P-1250	NH-1250	NG-1250
28.6-50.8	1.1/4"/2"	P-2000	NH-2000	NG-2000
47.6-76.2	1.7/8"-3"	P-3000	NH-3000	NG-3000